

From: [Saved by Windows Internet Explorer 7](#)
Subject: Specimen Label
Date: Friday, June 01, 2007 4:49:10 PM

[Click here to print this page](#)

[Close Window](#)

Specimen Label

TERMITAFOAM

A Specialty Foam for Structural Pest Control Use

For use with pesticides

Ideal for drywall and sub-slab foaming

Treats hard to reach areas - under concrete slabs, into framed walls, wall voids, plumbing walls

Excellent supplement to conventional treatment

Proven effective foaming agent

Flash Point greater than 200F

Principal Functioning Agents:

Sodium Lauryl Sulfate/Disodium Laureth 3 Sulfosuccinate Coconut Fatty Acid Monoethanolamide Ammonium Salt of Ethoxylated and Sulfated C8-10 Alcohols	36%
Inert Ingredients	64%
TOTAL	100%

Caution Keep out of reach of children

Net Contents: One Quart (0.95 Liter)

Termitafoam 2 rates will vary depending upon pesticide and foaming machines used. Expanded foam will normally last one to two hours prior to "draining" away.

Concrete Sub-Slab Foaming Rate: 3/4-2 oz. Termitafoam to 1 gallon water/pesticide solution. A "wet" foam is desired for sub-slab applications to adequately saturate the soil.

Dry Wall or Above Ground Foaming Rate: 4-6 oz. Termitafoam to 1 gallon water/pesticide solution. Dry wall foam should be light, dry, and maintain direct contact with the wood to ensure maximum absorption.

Helpful Hints:

ï For best results, use soft water with a neutral pH.

ï A "test wall" with a plexiglass covering is a good training aid to teach proper application skills.

1 cubic foot equals 7.5 gallons of expanded foam.

Contact Becker Underwood at 800-232-5907 for specific termiticide/foam expansion rates.

MIXING INSTRUCTIONS 1) Fill foam tank 1/4 - 1/2 full with water; 2) Add pesticide; 3) Add Termitafoam 2. 4) Complete filling of foam tank with water and mix for at least 1 minute (Unless otherwise specified by a pesticide manufacturer, use the listed mixing order).

If expanded foam is runny and thin:

1) Check hose connections for proper air mixing; 2) Check Termitafoam 2 rate mixed; 3) Adjust Termitafoam rates upward.

Users must calibrate and test their application equipment to determine exact foam dilution rates, expansion volumes, and application coverage. Applicators should check ppm distribution or wood structure absorption to determine if pesticide label rates have been achieved. A registered product containing Diatomaceous earth may be applied with Termitafoam 2.

CAUTION:

Keep out of reach of children. Avoid contact with skin and eyes. If in eyes, flush with water and contact physician. If swallowed, DO NOT INDUCE VOMITING. Contact physician immediately.

STORAGE AND DISPOSAL

1. CONTAINER DISPOSAL: Triple rinse (or equivalent). Offer for recycling or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities. Store in original container only and keep sealed. Store in closed storage area.

NOTICE: There are no warranties which extend beyond the description on the label hereof. The manufacturer, Becker Underwood, Inc., warrants this product to be as described on the label. The manufacturers' liability on this warranty is limited to return of the purchase price of this product. The buyer assumes all risks and liability resulting from the use of this product, whether used singly or in combination with other goods. The manufacturer neither assumes nor authorizes any person to assume for it any other liability in connection with the sale or use of this product.

Manufactured by:

Becker Underwood, Inc.

801 Dayton Avenue
Ames, IA 50010
515-232-5907
Fax 515-232-5961
www.bucolor.com

[Click here to print this page](#)

[Close Window](#)