# **EcoEXEMPT Products: Insecticide Concentrates**

# **ECOEXEMPT MC / ECOEMULSIFIER**

## Misting Concentrate Insecticide



Container Size: ½ gal each

**Active Ingredient:** 18.0% Rosemary Oil, 2.0% Cinnamon Oil, 2.0% Lemongrass Oil

#### **Product Information:**

- · For tank and tankless misting systems
- Quick control of mosquitoes, gnats, flies & other flying insects
- No phytotoxicity or staining
- . No drift or aquatic concerns
- Provides a stable microemulsion for up to 90 days with no agitation required when used with EcoEMULSIFIER
- · Exempt from EPA registration

## **Product Replaces:**

- Prescription Treatment HydroPy
- Riptide

## **Product Application Tips:**

- Always use EcoEMULSIFIER with EcoEXEMPT MC when diluting in water
- Mix at a 1:1 ratio of EcoEMULSIFIER to EcoEXEMPT MC in the tank systems, and at a 1:2 ratio in tankless systems

# Proper mixing is critical to product performance:

FOR TANK SYSTEMS - NO AGITATION

- · Fill tank halfway with water
- Mix 1 part EcoEMULSIFIER with 1 part EcoEXEMPT MC in a pail (1:1 ratio) and stir for 20 seconds, then add to storage tank
- Fill balance of the tank with water

#### FOR TANK SYSTEMS - WITH AGITATION

- It is recommended that the agitation function be turned off when using these products
- If agitation cannot be turned off, it is recommended to add 1 part EcoEMULSIFIER to 7 parts EcoEXEMPT MC (1:7 ratio)

#### FOR TANKLESS SYSTEMS

- Mix 1 part EcoEMULSIFIER with 2 parts EcoEXEMPT MC (1:2 ratio) in a pail, stir for 20 seconds
- Fill the injection tank with the ECOEXEMPT MC/ECOEMULSIFIER mixture

# **EcoEXEMPT Products: Insecticide Concentrates**

# **Troubleshooting Guide**

## **Problem:**

Clumping in tank

Spray equipment seals fail/leak/swell

### **Possible Causes/Solutions:**

- Make sure tank/equipment has been cleaned/triple rinsed
- Mixing is critical. Must use with EcoEMULSIFIER. The label instructions must be followed explicitly to form a proper microemulsion
- Replace all screens with 50 mesh or larger screens
- . If necessary, replace seals with Teflon seals
- Contact company for information on equipment component compatibility

## **Notes:**